

MT8836,37,38,39

# CABLE TIE TAG

USING UL APPROVED NYLON-66 ANTI-AGING AND WATER-PROOF



# MT8836,37,38,39 CABLE TIE TAG

A MT-8836-38 is a very practical marker tie cable tag, it can apply to various types of material tracking management.

B.Material: Using UL approved Nylon-66, anti-aging and water-proof.

## MT8836,37,38,39 RFID Cable Tie Tag Specification

Model No.	MT8836	MT8837	MT8838	MT8839
Length/diameter	18x30mm	30x200mm	20x128mm	20x128mm
Reading Distance(GK4001, EM9917 Reader)	50mm	50mm	50mm	50mm
Operating temperature	-40°C to 70°C	-40°C to 85°C	-40°C to 85°C	-40°C to 70°C
Storage temperature	-40°C to 80°C	-40°C to 100°C	-40°C to 100°C	-40°C to 80°C
Material	PVC	Nylon-66	Nylon-66	PVC
IP	67	67	67	67
Color(black/red/green/yellow)	Only white	4	4	2
<b>Chip available</b>				
GK4001 (125KHz, 64bit, R/O)	Y	Y	Y	Y
H4102 (125KHz, 64bit, R/O)	Y	Y	Y	Y
I-Code (13.56MHz, 512bit, R/W)	Y	Y	Y	Y
Temic E5557 (125KHz, 256bit, R/W)	Y	Y	Y	Y
Hitag 1 (125KHz, 2048bit, R/W)	Y	Y	Y	Y
Hitag 2 (125KHz, 256bit, R/W)	Y	Y	Y	Y

### Application:

- Telecommunication exchange equipment & extension tracking management.
- Logistic tracking management.
- Material e-automation management.

### Dimension: (unit: mm)

