

WS887X

RFID HAND WATCH

RFID WATCH IN VARIOUS DESIGNS



WS8871



WS8872



WS8873

WS8871,8872,8873 RFID Hand Watch Specification

Model No.	WS8871	WS8872	WS8873
Reading Distance	60mm	60mm	60mm
Base on GK4001 chip, with EM9917 Reader			
Operating temperature	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C
Storage temperature	-40°C to 80°C	-40°C to 80°C	-40°C to 80°C
Material	PVC	PVC	PVC
Shower proof	Y	Y	Y
Technology			
GK4001 (125KHz, 64bit, R/O)	Y	Y	Y
H4102 (125KHz, 64bit, R/O)	Y	Y	Y
I-Code I (13.56MHz, 512bit, R/W)	Y	Y	Y
Mifare I S50 (13.56MHz, 1KByte, R/W)	Y	Y	Y
Temic e5557 (125KHz, 256bit, R/W)	Y	Y	Y
Hitag 1 (125KHz, 2048bit, R/W)	Y	Y	Y
Hitag 2 (125KHz, 256bit, R/W)	Y	Y	Y
Legic 256 (13.56MHz, 256Byte, R/W)	Y	Y	Y
I-Code SLI (13.56MHz, 1024bit, R/W)	Y	Y	Y

Layout Plane

